



# BLUE RIBBON Sales & Services Corp.

## BULLDOG BD200 SETPOINT PUMP CONTROLLER

Dual setpoint controller that is easy to program. Controls submersible pumps in lift stations, and is designed to field calibrate the Birdcage Level Sensor.

### STANDARD FEATURES:

- Selectable pump alternation when used with two pumps to minimize pump wear. With alternation "On", a seal failure or over-temperature condition will force the non-failed pump to lead status and stop alternation.
- Alarm light for seal failure when used with a submersible pump that includes a moisture sensor.
- Alarm light for overheating when used with a pump that includes a thermostat. Pump is removed from service and can be brought back online manually or automatically when pump has cooled down.
- Runtime displayed by a front panel button.
- 24 VDC power for level transmitter
- 4-20 mA or voltage signal
- Nonvolatile memory, no batteries
- Test System function that simulates the process input to test programming or to insure the pumps are operating.
- User-selectable security lock-out of programming and/or setpoints.



The Bulldog BD200 Pump Controller provides versatile level control in a standard 1/4 DIN package.

This controller is versatile, simple, and inexpensive making it the ideal instrument for controlling dual pump lifting stations. Setpoints for ON/OFF and HI/LO alarms are easily set on the front panel. These same buttons also Enable/Disable pump alternation. Selectable time delay up to 60 seconds on power up for pump two prevents both pumps from starting at the same time and a large current draw. Alarms for pump seal failure and motor windings overheating are indicated by lights on the front panel. The dial can also display a runtime clock for each pump. An isolated 4-20 mA retransmission is standard. The front face is rated NEMA-4X for outdoor panel mounting. The BD-200 is also available with RS-232 or RS-485 protocol for connectivity with SCADA systems.

See reverse side for technical specifications and ordering guide.

Blue Ribbon reserves the right to make product improvements and amendments to the product specifications stated throughout this brochure without prior notification. Please contact the factory on all critical dimensions and specifications for verification.



A5BR-BD200.00



# BLUE RIBBON Sales & Services Corp.

Standard Specifications listed below.

Consult factory for further options, which may change the overall dimensions.

<b>Inputs</b>	4 (or 0) to 20 mADC or 2 (or 0) to 10 VDC selectable
<b>Input Impedence</b>	Current = 10 ohms, Voltage = 100 K ohms
<b>Output Ratings</b>	Control Relays: SPDT, 10A @ 240 VAC resistive, 1/4 hp @ 120 VAC, 1/3 hp @ 240 VAC Alarm Relays: SPST, 3A @ 240 VAC resistive, 1/10 hp @ 120 VAC
<b>Control Type</b>	On/Off, reverse (pump out) or direct (pump in) acting
<b>Accuracy</b>	± 0.25% of span ± 1 least significant digit
<b>Display</b>	Two 4 digit, 7 segment, 14.2mm (0.56") high LED's
<b>Resolution</b>	1 count
<b>Power Consumption</b>	7.5 VA maximum
<b>Electrical Supply</b>	100 to 240 VAC nominal, +10% to 15%, 50 to 400 Hz single phase; 132 to 240 VDC +10% to 15%
<b>Loop Powered Supply</b>	Isolated +24 VDC @ 50mA, regulated
<b>Temperature Range</b>	Operating Range: -10°C to +55°C (-14°F to +130°F) Storage Range: -40°C to +80°C (-40°F to +175°F)
<b>Humidity Range</b>	0 to 90% up to 40°C for non-condensing
<b>Seal Failure (Moisture Sensor)</b>	Power: 2.5 VDC Search Current: 3 micro amps Resolution: 10K to 500K ohms in 10K ohm steps
<b>Agency Approvals</b>	UL508, CE, FM  
<b>Memory Backup</b>	Non-volatile memory, no batteries
<b>Panel Cutout</b>	92mm X 92mm (3.622" X 3.622")
<b>Weight</b>	454 g (16 oz)
<b>Front Panel Rating</b>	IP66 (Type NEMA 4X)
<b>Options</b>	RS-232 or RS-485 with Mod bus protocol; Ethernet using TCP/IP
<b>Accessories</b>	Weatherproof Enclosures, NEMA 4X

## Ordering Guide:

**Example: BD200**

Part No.

477 Commerce Way, Suite 109, Longwood, FL 32750

Tel. (877) 677-8899 • Fax (407) 657-6622 • brsales@blueribboncorp.com • www.blueribboncorp.com